



OUR TARPS COVER ANY OPEN TOP TRAILER ON THE MARKET

	BOW OPTION	OVERVIEW	MODEL / TYPE	FABS / NEED TO KNOW
REMOVABLE BOWS	STEEL	ADJUSTABLE STEEL BOW	TRAILERS + BODIES up to 53'	Bow removal advised during loading to avoid damage. Recommended bow spacing 48".
	ALUMINUM	SOLID FORMED ALUMINUM ROD	TRAILERS + BODIES up to 53'	Bow removal advised during loading to avoid damage. Bows are custom fit per trailer width. Recommended bow spacing 48".
	NYLA BOW	SOLID NYLON ROD WITH UHV PROTECTIVE COVER	TRAILERS + BODIES up to 53'	205 degree maximum heat tolerance, with a 8" minimum and 12" maximum bow rise. Bow holders are billet aluminum. Bows do not need to be removed for loading. Recommended bow spacing 48".
	FLEXBOWS	1 3/8" FIBERGLASS	TRAILERS + BODIES up to 53'	Bow holders are cast aluminum. Bows do not need to be removed for loading. Recommended bow spacing 48".
BOW SYSTEMS	SWING AWAY	HEAVY DUTY STEEL BOWS WITH PULL ROPE <i>Swing away for safe and easy operation</i>	TRAILERS up to 48'	Safe operation from ground; helps eliminate damage from loaders. Available in 8" low rise and 12" high rise. Bows must swing open when loading.
	HEAVY DUTY WITH CENTER RIDGE TUBE	HEAVY DUTY 1 1/4" STEEL ADJUSTABLE BOW	TRAILERS up to 53'	Bow spacing of 10' with use of a ridge pole. Bow rise of 10". Bows swing to one side. Bows do not need to be removed for loading.
	MAX-DUTY STEEL WITH CENTER RIDGE TUBE	HEAVY DUTY 3" STEEL ADJUSTABLE BOW	TRAILERS up to 53'	Bow spacing of 10' with use of a ridge pole. Bow rise of 10". Bows swing to one side. Bows do not need to be removed for loading.